



<b>PRODUCT DATA SHEET</b>	Page: 1 of 2
	US Revision: 1
<b>RDI-DECO ACRYL BLUE</b>	Date: 01/01/2014
	Supersedes:
	<b>RDI 2</b>

## DESCRIPTION OF THE PRODUCT

USE	Waterborne one component flat acrylic paint, for interior walls and ceilings. Very appropriate for application over a wide variety of substrates.  This coating contains an antimicrobial agent to prevent microorganisms from degrading the dried paint film.
FEATURES	High covering capacity - Easy to apply because of a high percentage of binder - Easy to clean – Non-yellowing.
SUBSTRATES	Plaster, gyproc, bricks, concrete, old paints, wallpaper.
SYSTEM:	Slightly porous substrates: Direct application of the first coat of Deco Acryl on the substrate.  On more porous substrates the first coat of Deco Acryl diluted up to 20% with RD-Unifix Very porous substrates: <ul style="list-style-type: none"> <li>• Primer: 1 coat of impregnation: UNIFIX.</li> <li>• Basecoat: Deco Acryl</li> <li>• Topcoat: Deco Acryl Blue</li> </ul>

## APPLICATION INSTRUCTIONS

PREPARATION OF THE SUBSTRATE:	The substrate has to be clean, dry, and free of dust.
APPLICATION CONDITIONS	Ambient temperature: above 45°F R.H.: max. 90%
APPLICATION MEANS	Brush, roller or airless (nozzle: 013–015)
DILUTION :	Water/RD-Unifix
CLEANING OF TOOLS:	Water
COVERAGE :	Theoretical coverage per Gallon per coat: 220 sq ft at 3 mills DFT
PARTICULARITIES	Mix before use.



<b>PRODUCT DATA SHEET</b>	Page: 2 of 2
	US Revision: 1
	Date: 01/01/2014
<b>RDI-DECO ACRYL BLUE</b>	Supersedes:
	<b>RDI 2</b>

<b>TECHNICAL DATA</b>
-----------------------

FINISH:	Flat
COLOURS :	White
SOLIDS CONTENT :	In weight: ca. 59% In volume: ca. 43%
VOC CONTENT:	Max 30g/L
DENSITY:	Ca. 1.4
FLASH POINT :	Not flammable.
VISCOSITY:	100 - 150 P (Brookfield 20 Rpm)
DRYING TIME:	To touch: 2 hours Recoatable: 4 hours.
PACKAGING:	1 and 5 Gallon units
STORAGE STABILITY:	12 months, keep away from frost.

<b>SAFETY DATA</b>
--------------------

The safety data sheet is available on request.

These specifications are given for information. Since the manufacturer is not able to check the right application of the products, he cannot accept any responsibility for it. This technical data sheet replaces all previous editions.