



PDI DECO ACRVI BURBI E	Supersedes:
RDI-DECO ACRYL PURPLE	
PRODUCT DATA SHEET	US Revision: 1 Date: 01/01/2014
	Page: 1 of 2

## DESCRIPTION OF THE PRODUCT

USE Waterborne one component flat acrylic paint, for interior walls and ceilings.

Very appropriate for application over a wide variety of substrates.

This coating contains an antimicrobial agent to prevent mold from degrading

the dried paint film.

FEATURES High covering capacity - Easy to apply because of a high percentage of binder -

Easy to clean - Non-yellowing.

SUBSTRATES Plaster, gyproc, bricks, concrete, old paints, wallpaper.

SYSTEM: Slightly porous substrates:

Direct application of the first coat of Deco Acryl on the substrate.

On more porous substrates the first coat of Deco Acryl diluted up to 20% with

**RD-Unifix** 

Very porous substrates:

• Primer: 1 coat of impregnation: UNIFIX.

Basecoat: Deco AcrylTopcoat: Deco Acryl Purple

## APPLICATION INSTRUCTIONS

PREPARATION OF THE SUBSTRATE:

The substrate has to be clean, dry, and free of dust.

APPLICATION

Ambient temperature: above 45°F

CONDITIONS R.H.: max. 90%

APPLICATION

**MEANS** 

Brush, roller or airless (nozzle: 013-015)

DILUTION: Water/RD-Unifix

**CLEANING OF** 

TOOLS:

Water

COVERAGE: Theoretical coverage per Gallon per coat:

220 sq ft at 3 mills DFT

PARTICULARITIES Mix before use.





PRODUCT DATA SHEET  RDI-DECO ACRYL PURPLE	RDI 3
	Supersedes:
	Date: 01/01/2014
	US Revision: 1
	Page: 2 of 2

## TECHNICAL DATA

Flat FINISH:

COLOURS: White

**SOLIDS CONTENT:** In weight: ca. 59%

In volume: ca. 43%

VOC CONTENT: Max 30g/L

DENSITY: Ca. 1.4

FLASH POINT: Not flammable.

VISCOSITY: 100 - 150 P (Brookfield 20 Rpm)

To touch: 2 hours **DRYING TIME:** 

Recoatable: 4 hours.

PACKAGING: 1 and 5 Gallon units

**STORAGE** 

STABILITY:

12 months, keep away from frost.

## SAFETY DATA

The safety data sheet is available on request.

These specifications are given for information. Since the manufacturer is not able to check the right application of the products, he cannot accept any responsibility for it. This technical data sheet replaces all previous editions.

RD Coatings USA 167 Avon Street, Stratford, CT 06615 P: 203-380-9477 F: 203-380-9488 www.rdcoatingsusa.com